## Single Action Lock Nut Hydraulic Cylinder x 70 units

Jack capacity: 50 MT

With mechanical load holding for extended periods of time

• Working pressure: 630 BAR [9,000 PSI]

Max operation pressure: 700 BAR [10,000 PSI]

Stroke: 150 mm

Collapsed height: 280 mm
Out-side diameter: Ø 125 mm
Inner diameter: Ø 100 mm

• Include: a) Flange size 140 x 140 mm with 4 holes of Ø ½", b) Two lifting lugs, c) Tilt saddle,

d) "T" connection port with M16 X 1.5 with TWO MALE quick couplers @ 10,000 PSI

## Single Action Power Pack 7.50 HP [5.50 kW] x 2 units

For max 70 jacks of 50 MT

• Working pressure: 630 BAR [9,000 PSI]

Max operation pressure: 700 BAR [10,000 PSI]

Valve type: Manual
Flow: 5 to 10 L/minute
Oil tank capacity: 200 liters
Input Power: 380 V, 50 Hz, 3 P

Include: a) Lifting hooks 4x, b) Forklift access on bottom of tank (4" height).

## Hydraulic Hose of 7.0 m length @ 10,000 PSI x 120 units

Include: TWO FEMALE quick couplers on both ends, M16 X 1.5





